


QUALITY ★★ ★

Speaker Wire SP-25

Loudspeaker cable, 2x2.5mm², mini coil

Excellently made stereo loudspeaker cable wound on to a mini coil. This loudspeaker cable is suitable for amplifier performances of up to around 120 watts of power per amplifier channel. The use of oxygen-free copper (OFC) as the conducting material ensures that an extremely clear and true-to-life sound can be achieved with this loudspeaker cable. The cable has also been made from very many ultrathin stranded copper wires – each individual wire possesses a cross-section of around 0.125 mm. This complex design means that the cable is particularly conductive and flexible throughout.



Features


- ✓ Made in Switzerland
- ✓ Individually insulated copper wires
- ✓ Stereo speaker cable
- ✓ For amplifier performances of up to 120 watts
- ✓ Robust plastic sheathing
- ✓ OFC – oxygene free copper
- ✓ highly flexible cable

Technical Data

Cable cross-section	2 x 2.5 mm ²
Cable geometry	Flat

Designation	Art. No.	Unit	Colour
Speaker Wire SP-25 / 1000	102	10 m	Clear
Speaker Wire SP-25 / 2000	106	20 m	Clear
Speaker Wire SP-25 / 3000	108	30 m	Clear

CONNECTIONS



Terminal Terminal

SIGNALTYPE



Audio

SIGNALDIRECTION



Bi-Directional

IN
 SPEAKER

OUT
 PLASMA/LCD | PROJECTOR