



QUALITY ★★★★★

Transmission Max S

Digital satellite cable

Preassembled digital satellite cable for the transmission of high-resolution audio and image data. External interference stands no chance thanks to the use of a very compact sheath current filter. The inner conductor used in this very well-made satellite cable is manufactured from silver-plated oxygen-free copper (SPC); its fourfold shielding means that it is particularly suited for the transmission of sensitive HDTV signals! A moulded plug with metal sleeve ensures that the transmission of signals is particularly stable even at the critical material transitions.



Features

- ✓ Incl. removable sheath-current filter
- ✓ >120 dB Shielding
- ✓ Full HD – Video
- ✓ fourfold shielding
- ✓ Robust plastic sheathing
- ✓ Solid full-metal plug
- ✓ 24 ct gold plated plug
- ✓ SPC - silver-plated copper
- ✓ Coaxial cable layout
- ✓ 75 ohm wave impedance


Technical Data

Shielding dimension	120 dB
Capacity	52 pF/m
Inner conductor material	SPC/OFC - silver-plate oxygen-free copper
Cable sheathing	plastic
Shielding quantity	fourfold shielding
Shielding material	2 x aluminium foil + 2 x copper braid
Plug design	Metal plug with plastic sleeve
Characteristic wave impedance	75 Ω
Cable geometry	Round
Plug type	Straight

Designation	Art. No.	Unit	Colour
Transmission Max 170 S	2890	1.7 m	anthracite
Transmission Max 220 S	2891	2.2 m	anthracite
Transmission Max 320 S	2892	3.2 m	anthracite
Transmission Max 510 S	2893	5.1 m	anthracite
Transmission Max 750 S	2894	7.5 m	anthracite
Transmission Max 1000 S	2895	10 m	anthracite
Transmission Max 170 S	2910	1.7 m	silver
Transmission Max 220 S	2911	2.2 m	silver
Transmission Max 320 S	2912	3.2 m	silver
Transmission Max 510 S	2913	5.1 m	silver
Transmission Max 750 S	2914	7.5 m	silver
Transmission Max 1000 S	2915	10 m	silver



CONNECTIONS



SIGNALTYPE



SIGNALDIRECTION



Bi-Directional

IN

TV | TUNER BOX | HDD RECORDER | SAT RECEIVER

OUT

SAT