



QUALITY ★★ ★



Designation	Art. No.	Unit	Colour
Transmission Plus 170	2810	1.7 m	white
Transmission Plus 220	2811	2.2 m	white
Transmission Plus 320	2812	3.2 m	white
Transmission Plus 500	2813	5.1 m	white
Transmission Plus 750	2814	7.5 m	white
Transmission Plus 1000	2815	10 m	white
Transmission Plus 170	2820	1.7 m	silver
Transmission Plus 220	2821	2.2 m	silver
Transmission Plus 320	2822	3.2 m	silver
Transmission Plus 500	2823	5.1 m	silver
Transmission Plus 750	2824	7.5 m	silver
Transmission Plus 1000	2825	10 m	silver

Transmission Plus

Digital antenna cable

Prefabricated digital antenna cable for transmitting high-definition audio and image data. The inner conductor used in this very well-made antenna cable is manufactured from oxygen-free copper (OFC); its fourfold shielding means that it is particularly suited for the transmission of sensitive HDTV signals!

Features


- ✓ Full HD – Video
- ✓ >120 dB Shielding
- ✓ fourfold shielding
- ✓ Robust plastic sheathing
- ✓ 24 ct gold plated plug
- ✓ OFC – oxygene free copper
- ✓ Coaxial cable layout
- ✓ 75 ohm wave impedance

Technical Data

Shielding dimension	120 dB
Capacity	52 pF/m
Inner conductor material	OFC – oxygene free copper
Cable sheathing	plastic
Shielding quantity	fourfold shielding
Shielding material	2 x aluminium foil + 2 x copper braid
Plug design	Enclosed plastic plug
Characteristic wave impedance	75 Ω
Cable geometry	Round
Plug type	Straight
Shielding rate	110dB



CONNECTIONS



Antenna-Plug Antenna-Plug

SIGNALTYPE



Audio Video

SIGNALDIRECTION



Bi-Directional

IN

HDD REC. | PLASMA/LCD | TV | VIDEO REC. | TUNER BOX | AV RECEIVER

OUT

DVD RECORDER | SAT RECEIVER | VIDEO RECORDER | HDD RECORDER